
AgendaV Documentation

Release 1.2.3

Jorge López Pérez

Sep 08, 2022

Contents

1	Release notes	3
1.1	1.2.3 (2011-11-08)	3
1.2	1.2.2 (2011-10-25)	3
1.3	1.2.1 (2011-10-24)	3
1.4	1.2 (2011-10-17)	4
1.5	1.1.1 (2011-09-24)	4
2	Installation and configuration	5
2.1	Installation	5
2.2	Configuration	6
2.3	Troubleshooting AgenDAV	11
3	Translating AgenDAV	13
3.1	How to add a translation	13
	Index	15

AgendaV is a CalDAV web client which features an AJAX interface to allow users to manage their own calendars and shared ones. It's released under the GPLv3 license.

Contents:

1.1 1.2.3 (2011-11-08)

This release fixes some bugs with am/pm indicators under some circumstances, editing recurring events, include_path problems and other bugs.

It also introduces dynamic text color calculation and new default calendar colors, so it's recommended to remove the following settings from `config.php`:

- `default_calendar_color`: now the first color from `calendar_colors` is used
- `additional_calendar_colors`: this option has been replaced by `calendar_colors`

Copy `calendar_colors` definition from `config.php.template` to your `config.php`

This release requires no database upgrades.

1.2 1.2.2 (2011-10-25)

This release fixes important issues with recurrent events. It also fixes the am/pm indicator on times.

It requires no database upgrades.

1.3 1.2.1 (2011-10-24)

This release mainly fixes issues with timezone differences and Daylight Save Time problems.

Also updates iCalcreator library to latest version (2.10.15) and qTip2.

It requires no database upgrades.

1.4 1.2 (2011-10-17)

- DB schema needs to be altered. UTF8 wasn't being used by default, and sessions table wasn't using InnoDB. Apply the changes on `sql/changes/1.1.1_to_1.2.mysql`, which are the following:

```
ALTER DATABASE agendav CHARACTER SET utf8 COLLATE utf8_general_ci;
ALTER TABLE sessions CONVERT TO CHARACTER SET utf8;
ALTER TABLE sessions ENGINE InnoDB;
ALTER TABLE shared CONVERT TO CHARACTER SET utf8;
```

- Main configuration file (`config.php`) has been completely **rewritten** to make it easier to write. Please, use the provided `config.php.template` as the base for a new `config.php`
- Interface translation and timezone configuration is now possible in AgendaV. Please, make sure you set correct values on `config.php`
- AgendaV has lots of corrections and fixes. See the `CHANGELOG`

1.5 1.1.1 (2011-09-24)

- Fix DB schema. Wasn't properly updated on `sql/schema.sql`, which caused a problem with sessions

To correct this issue without completely recreating your current database, run the following two queries:

```
CREATE INDEX last_activity_idx ON sessions(last_activity);
ALTER TABLE sessions MODIFY user_agent VARCHAR(120);
```

- Remove LDAP dependency. AgendaV now authenticates against CalDAV server.

Before this change, AgendaV authenticated users at first using LDAP, and then your CalDAV server had to authenticate them again. With this change, AgendaV completely relies on your CalDAV server.

Installation and configuration

2.1 Installation

In this section you will be able to install AgenDAV.

2.1.1 Prerequisites

AgenDAV 1.2.3 requires the following software to be installed:

- A CalDAV server (developed mainly with [DAViCal](#))
- A web server
- PHP > 5.2
- PHP mbstring extension
- MySQL > 5.1

2.1.2 Downloading AgenDAV and uncompressing

AgenDAV 1.2.3 can be obtained at [AgenDAV official webpage](#), but you can use GitHub to download latest version. Have a look at <http://github.com/adobo/agendav>.

Uncompress it using `tar`:

```
$ tar xzf adobo-agendav-...tar.gz
$ cd adobo-agendav-.../
```

2.1.3 Database and tables

AgenDAV needs a MySQL database with several tables created. There is a file called `schema.sql` inside the directory `sql/` which contains the table schemas.

Create an user in MySQL like this:

```
$ mysql -uroot -p
Enter password:
[...]
mysql> GRANT ALL PRIVILEGES ON agendav.* TO agendav@localhost IDENTIFIED BY
↪ 'yourpassword'
mysql> CREATE DATABASE agendav CHARACTER SET utf8 COLLATE utf8_general_ci;
mysql> FLUSH PRIVILEGES;
mysql> ^D
```

And then run the schema creation file:

```
$ mysql -uagendav -p agendav < sql/schema.sql
Enter password:
$
```

Now your database is ready.

2.1.4 Configuring Apache web server

Apache has to be configured to point to `web/public` directory, using its own `VirtualHost` or just an `Alias`.

Example using a dedicated virtualhost:

```
<VirtualHost 1.2.3.4:443>
  ServerAdmin admin@email.host
  DocumentRoot /path/to/agendav/web/public
  ServerName agendav.host
  ErrorLog logs/agendav_error_log
  CustomLog logs/agendav_access_log common
</VirtualHost>
```

Example using the `Alias` directive:

```
Alias /agendav /path/to/agendav/web/public
```

Other web servers

AgendaV should work on all other web server software if they support PHP scripts, but this is untested.

2.2 Configuration

Configuring AgendaV requires modifying some PHP text files located in the `web/config/` directory.

The following files are usually found as `filename.php.template`, so make a copy of them with the correct file name to make them work.

Note: `ldap.php` was removed in AgendaV 1.1.1

2.2.1 General configuration (config.php)

`config.php` file specifies general options about AgendaV environment. It loads a set of default option values from `defaults.php`, but it is recommended to configure all of the following variables.

Please, do not modify `defaults.php`, as it is a file that updates on every AgendaV upgrade to avoid problems if you forget any configuration setting.

base_url

Specify here your full public URL to access AgendaV, adding a trailing slash. Example:

```
$config['base_url'] = 'https://agendav.host/';
```

show_in_log

Array of logging levels which will appear in logs. Possible logging levels are:

- **ERROR:** error messages, recommended
- **INFO:** informational messages, recommended
- **AUTHERR:** authentication errors
- **AUTHOK:** successful authentications
- **INTERNALS:** AgendaV internal processing actions, not recommended unless you are having problems or you want to debug AgendaV
- **DEBUG:** CodeIgniter internal debug. Do not enable unless you know what you are doing

Example:

```
$config['show_in_log'] = array('ERROR', 'INFO', 'AUTHERR', 'AUTHOK');
```

log_path

Full path where logs will be created. Add a trailing slash. Example:

```
$config['log_path'] = '/var/log/agendav/';
```

Make sure the user that runs your web server has write rights on that directory.

encryption_key

Random string which will be used to encrypt some cookie values.

cookie_prefix

Prefix that should be prepended to your cookie names. Useful if you have several sites hosted on the same hostname and you want to avoid name collisions

cookie_domain

Domain the cookie will be defined for. Use `.domain.tld` or `full.host.domain.tld`, depending on what you want.

cookie_path

Path the cookie will be defined for.

cookie_secure

Create cookies only for use in https environments. Set it **TRUE** if your users access AgendaV via https.

proxy_ips

Comma delimited IPs of your proxies, which will make CodeIgniter framework to trust the `HTTP_X_FORWARDED_FOR` header. Leave it blank if your AgendaV installation isn't being accessed via HTTP proxy.

site_title

Title of every page

logo

Image filename which will be used as a logo. Has to be a valid filename placed inside `web/public/img/` directory.

footer

Text to be placed in the footer.

logout_redirect_to

When logging out from AgendaV, the URL the user will be redirected to.

Can be left empty to redirect user to login page again.

additional_js

Array of additional JavaScript files which you will be loading on every page. They have to be placed inside `web/public/js`

show_public_caldav_url

Whether to show CalDAV URL links or not in the edit dialog

See also:

[*public_caldav_url*](#)

default_language

Language to be used in AgendaV interface.

Currently available options (languages):

- `de_DE`: German
- `en_US`: English (United States)
- `es_ES`: Spanish

New in version 1.2.

default_time_format

Preferred time format: 12 hours (e.g. 3pm / 2:30am) or 24 hours (e.g. 15:00 / 2:30).

Set this option using a **string** ('12' or '24').

New in version 1.2.

default_date_format

Preferred date format to be used inside date fields. Possible values are:

- `ymd`: e.g. 2011/10/22
- `dmy`: e.g. 22/10/2011
- `mdy`: e.g. 10/22/2011

New in version 1.2.

default_first_day

Which day should be considered the first of the week. Starting with 0 (Sunday), 1 means Monday and so on.

Use a numerical value, not an integer.

New in version 1.2.

default_timezone

Timezone to be used internally. Will be used for recalculating other timezone dates and hours to be sent to the browser, ignoring browser configured timezone.

Make sure you use a valid timezone from <http://php.net/timezones>

New in version 1.2.

default_calendar_color

Deprecated since version 1.2.3.

Default background and foreground colors for calendars. Has to be specified as an associative array. Example:

```
// Default background color: #B5C7EB
// Default foreground (text) color: #000000
$config['default_calendar_color'] = array('B5C7EB' => '000000');
```

additional_calendar_colors

Deprecated since version 1.2.3.

List of selectable background and foreground color combinations. Specify them as an associative array. Example:

```
// background color => foreground color
$config['additional_calendar_colors'] = array(
    'FAC5C0' => '000000',
    'B7E3C0' => '000000',
    'CAB2FC' => '000000',
    'F8F087' => '000000',
    'E6D5C1' => '000000',
    'FFC48C' => '000000',
    'DAF5FF' => '000000',
    'C4C4BC' => '000000',
);
```

calendar_colors

List of selectable background colors. Foreground color will be automatically calculated depending on the darkness of the color. Specify them as an array. Example:

```
$config['calendar_colors'] = array(
    '9CC4E4',
    '3A89C9',
    '107FC9',
    'FAC5C0',
    'FF4E50',
    'BD3737',
    'C9DF8A',
    '77AB59',
    '36802D',
    'F8F087',
    'E6D5C1',
    '3E4147',
);
```

2.2.2 Database configuration (database.php)

`database.php` contains how to connect to your MySQL database. Just follow inline comments, it's pretty straight forward.

2.2.3 CalDAV specific options (caldav.php)

Here you will configure every single aspect of your CalDAV server.

caldav_url

The `_internal_` URL used by AgendaV to connect to your CalDAV server. The placeholder `%u` will be replaced by current user.

Needs a trailing slash.

Example:

```
$config['caldav_url'] = 'http://10.0.0.12/caldav.php/%u/';
```

For user4 Will become:

<http://10.0.12/caldav.php/user4/>

public_caldav_url

The URL that will be shown to users if `show_public_caldav_url` is enabled. It's not used for internal connections. Placeholder `%s` will be replaced by current username and calendar.

Needs a trailing slash.

Example:

```
$config['public_caldav_url'] = 'https://public.caldav.tld/caldav.php/%s/';
```

Will become for user `user2` and calendar `myhomecalendar`:

<https://public.caldav.tld/caldav.php/user2/myhomecalendar/>

owner_permissions

List of DAV permissions used for the calendar owner when sharing a calendar. As DAV ACLs are used, when editing a calendar sharing options a full ACL has to be built with the following structure:

- Permissions given to the owner (this option)
- Permissions given to granted users (`share_permissions`)
- Permissions given to other users (`default_permissions`)

Please, refer to your CalDAV server documentation to know which permissions does it support.

For DAViCal you can follow [Permissions page on DAViCal wiki](#). Default values of this option will work all right for DAViCal.

See also:

Used in conjunction with options `share_permissions` and `default_permissions`.

share_permissions

List of DAV permissions used for granted users when another user shares a calendar with them.

Please, refer to your CalDAV server documentation to know which permissions does it support.

Default value lets users to read and write on shared calendars. AgendaV doesn't support at this moment to select whether you want read or shared rights.

See also:

Used in conjunction with options `owner_permissions` and `default_permissions`.

default_permissions

List of DAV permissions used for users which are not owner neither granted users when some user shares a calendar with other ones.

Please, refer to your CalDAV server documentation to know which permissions does it support.

Default value lets users just to make free/busy queries in DAViCal.

See also:

Used in conjunction with options *owner_permissions* and *share_permissions*.

2.2.4 Other configuration files

Advanced options (advanced.php)

This file should be kept untouched unless you know what you are trying to modify. It contains several options that make AgenDAV work by default.

2.3 Troubleshooting AgenDAV

If you are having problems with AgenDAV, do the following changes to enable more verbose debugging:

Edit `web/config/config.php` and add the value `INTERNALS` inside `show_in_log` variable. For example:

```
$config['show_in_log']= array('ERROR','INFO','AUTHERR','AUTHOK','INTERNALS');
```

Check AgenDAV logs (make sure you have Check AgenDAV logs (make sure you have a valid path configured in *log_path* and the user which runs the webserver has writing access to it) and your webserver logs.

Translating AgenDAV

AgenDAV translation system is based on labels which get translated into full sentences/paragraphs. They can contain placeholders which get replaced by the system depending on the context.

3.1 How to add a translation

Consider the `en_US` language to be the master reference language file.

1. Copy the directory `web/lang/en_US` to a new directory inside `web/lang` with the name of the locale of the new language. For example:

```
$ cp -R web/lang/en_US web/lang/fr_FR
```

2. Rename `en_US.php` inside `fr_FR/` directory to `fr_FR.php`
3. Edit all strings on the file. Make sure you save it using UTF-8 encoding.
4. Search the corresponding [CodeIgniter translation](#) and download its zip file.
5. Uncompress the CodeIgniter translation into `web/application/language`
6. Edit `web/config/languages.php` and add a new entry like this:

```
$config['lang_rels']['fr_FR'] = array(  
    'codeigniter' => 'french',  
);
```

This supposes the language file you downloadad for CodeIgniter resulted in a directory called `french/`

7. You're done! Set `default_language` to your new language name (`fr_FR` in our example)

A

additional_calendar_colors
 configuration value, 9
additional_js
 configuration value, 8

B

base_url
 configuration value, 7

C

caldav_url
 configuration value, 10
calendar_colors
 configuration value, 9
configuration value
 additional_calendar_colors, 9
 additional_js, 8
 base_url, 7
 caldav_url, 10
 calendar_colors, 9
 cookie_domain, 7
 cookie_path, 7
 cookie_prefix, 7
 cookie_secure, 7
 default_calendar_color, 9
 default_date_format, 8
 default_first_day, 8
 default_language, 8
 default_permissions, 10
 default_time_format, 8
 default_timezone, 8
 encryption_key, 7
 footer, 8
 log_path, 7
 logo, 8
 logout_redirect_to, 8
 owner_permissions, 10
 proxy_ips, 7

 public_caldav_url, 10
 share_permissions, 10
 show_in_log, 7
 show_public_caldav_url, 8
 site_title, 7

cookie_domain
 configuration value, 7
cookie_path
 configuration value, 7
cookie_prefix
 configuration value, 7
cookie_secure
 configuration value, 7

D

default_calendar_color
 configuration value, 9
default_date_format
 configuration value, 8
default_first_day
 configuration value, 8
default_language
 configuration value, 8
default_permissions
 configuration value, 10
default_time_format
 configuration value, 8
default_timezone
 configuration value, 8

E

encryption_key
 configuration value, 7

F

footer
 configuration value, 8

L

log_path

- configuration value, 7
- logo
 - configuration value, 8
- logout_redirect_to
 - configuration value, 8

O

- owner_permissions
 - configuration value, 10

P

- proxy_ips
 - configuration value, 7
- public_caldav_url
 - configuration value, 10

S

- share_permissions
 - configuration value, 10
- show_in_log
 - configuration value, 7
- show_public_caldav_url
 - configuration value, 8
- site_title
 - configuration value, 7